

e-STUDIO™ 2802AF

- > Black & White MFP
- > 28 PPM
- > Small Workgroup
- > Copy, Print, Scan, Fax
- > Mobile Enabled

Don't let the small size fool you. This compact Toshiba e-STUDIO2802AF combines a letter sized footprint with a ledger sized capability. You'll find all the functions you need, including copying, printing and scanning—even faxing. First copy out time is 6.5 seconds, with impressive 2,400 x 600 dpi output delivered at 28 pages per minute. The Reversing Automatic Document Feeder (RADF) and Automatic Duplex Unit (ADU) enable two-sided copying and printing that save money and resources. An Ethernet network interface and optional wireless connectivity ensure seamless integration, while the unique e-BRIDGE Print & Capture application allows mobile users to share the device as well.



Specifications

Copying/Printing Process Type	Indirect Electrostatic Photographic Method Desktop
Original Scanning Method	Contact Image Sensor (CIS)
Resolution	2400 x 600 dpi (with Smoothing)
Gradation	256 Steps
Original Platen Type	Fixed Hard Platen, 50-Sheet RADF (14-28 lb)
Available Original Size	ST-R to LD
Available Paper Size	Drawer: LT Only Stack Feed Bypass: ST-R, LT, LG, LD, Envelope
Paper Supply	Standard: Drawer (250 Sheets x 1) Stack Feed Bypass (50 Sheets)
Available Paper Weight	Drawer: 17-20 lb Stack Feed Bypass: 14-120 lb Index Auto Duplexing Unit: 17-20 lb
Paper Exit	Face Down/Inner Tray
Warm-up Time	Approx. 18 Seconds (Scanner Function Available During Warm-Up)
Counter	Electronic Counter (Indication by LCD Display)
Memory	512 MB
Department Codes	100
Power Supply	115 Volts, 12 Amps
Power Consumption	Maximum: 1.5kW
Dimensions	Approx. 15.3" x 21.25" x 20" (W x D x H)
Weight	Approx. 58.3/62.7 lb
Special Features	Energy Saver, Auto Sleep Mode, Department Code
Max Duty Cycle	64K Copies
Certifications	Energy Star V3.0, EPEAT (GOLD) & WEE (Argentina Model) + RoHS Compliant
Worldwide Safety Stds.	UL, GS, CE, CDRH, SASO, IRAM, EAC, CCC
Black Toner Yield	14.6K Impressions @ 6%

Copy Specifications

Copying Speed	28 PPM
Original Scan Speed	25 SPM (by Using RADF)
Scan Resolution	600 x 600 dpi (for Copying)
First Copy Time	Less Than 6.5 Seconds
Original/Copy Size	ST-R to LD
Original Mode	Photo, Text/Photo, Text, Background Erase
Image Density Control	Automatic/Manual (11 Steps)
Reproduction Ratio	Zoom: 25% to 400% in 1% Increments
Multiple Copying	Up to 999 Copies (Ten Key Input)
Special Features	Department Codes (100), Interrupt, APS/AMS, Auto Job Start, Automatic Sort Mode, ID Card Copy, One Touch Key (2)

Print Specifications (Standard)

Printing Speed	28 PPM
Printing Resolution	2400 x 600 dpi (with Smoothing)
Interface	Standard: 10/100 Base-T, USB 2.0 Optional: IEEE802.11 b,g,n
PDL	PCL 6 Emulation
USB Direct Printing	JPEG, TIFF, PDF (Only PDF Created by MFP Can Be Printed)
Support OS	Windows 7, 8, 8.1, 10, 2008R2, 2012, 2012 R2, (WHQL), CUPS PCL Unix, Linux 5.10.x, 6.5.x

Scan Specifications (Standard)

Connection Type	Standard: 10/100 Base-T Optional: IEEE802.11 b,g,n
Scanning Resolution	100/150/200/300/400/600 dpi
Scanning Speed	25 SPM (BW) at 600 dpi, 22 SPM (Color) @ 200 dpi, 13 SPM @ 300 dpi
Scan Agent	Scan to File, SMB, FTP, Scan to Email, Scan to USB, TWAIN IOS & Android Support Via e-BRIDGE Print & Capture App (Free on iStore or Play)

Paper Handling

Reversing Automatic Document Feeder (RADF)

Stack Capacity	50 Sheets
Original Setting	Face Up
Original Paper Size	ST-R to LD
Original Paper Weight	14-28 lb

FAX Specifications (e-STUDIO2802AF Only)

Compatibility	Super G3, G3
Image Format on PSTN	JBIG, MMR, MR, MH
Document Size	ST-R-LD
Modem Speed	33.6 kbps to 2.4 kbps (Automatic Fallback)
Transmission Speed	Approx. 3 Seconds
Communication Protocols	ITU-T T.30
Memory Transmission	Max 256 Jobs, 220 Destinations/Job, 384 Pages/File
Options	
Cabinet	ST-2505F
Wireless LAN Module	GN-1080
Harness for Coin Controller	GQ-1131



Windows 7 Compatible
Windows 8 Compatible
Windows 10 Compatible

Designs and Specifications subject to change without notice. For best results and reliable performance, always use supplies manufacturer or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 6% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system.

© 2015 Toshiba of Canada Limited
Inv. Code: CE-ES2802AF-B

Corporate Office

75 Tiverton Court
Markham, Ontario
L3R 4M8

Phone: (905) 470-3500
Fax: (905) 470-3459
Website: www.toshiba.ca